



# WIDE FORMAT INKJET PRINTABLE TEXTILES LINEN FR

*engineered by AURORA®*



Spun yarns give this fire retardant polyester fabric the look and feel of cotton table linens. Compatible with Latex and UV-cured inks. Printable on both sides.

- 100% Polyester
- Print both sides
- Treated to meet the NFPA 701 small scale flammability standard
- Great choice for table drapes, trade show displays, custom upholstery, theatrical displays, home/office décor, temporary outdoor banners

## PRINTABLE TEXTILES LINEN FR

WEIGHT OZ/MIL	LINER	WIDTH INCHES	WIDTH MM	LINEAL FEET	CORE	CODE NUMBER
7.0/17.0	-	30	762	30	3	67-82356
-	-	60	1524	300	3	82357

Visit [mohawkconnects.com](http://mohawkconnects.com) for more complete stocking info.

## COMPATIBILITY

LATEX	ECO-SOLVENT	SOLVENT	UV-CURED
✓✓✓	✗	✗	✓✓✓

- ✓✓✓ *Excellent*  
✓✓ *Good*  
✓ *Fair*  
✗ *Not Compatible*

# PRINTABLE TEXTILES LINEN FR

## TYPICAL PERFORMANCE VALUES

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material or his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Ink dry time: rapid drying depending upon type and amount of ink, relative humidity and temperature

Chemical resistance: not designed to be chemical resistant

Handling requirements: due to absorptive nature of the coating, avoid touching the coated surface with bare skin. Always wear chemical resistant gloves when handling inkjet-coated materials. Rolls are supplied with the coated surface wound out.

Durability outdoor: not designed for outdoor use

Solvent resistance: not designed to be solvent resistant

Printing temperature: 60 - 85°F / 40 - 60%RH

Display use: 60 - 85°F

Ideal storage conditions: 68 - 75°F

Shelf life: two years at ideal storage conditions, stored in original packaging

## PHYSICAL CHARACTERISTICS

PROPERTY	TYPICAL VALUE	UNIT	TEST METHOD
Material	100% Polyester		
Weave	Plain		
Weight	7.0	oz/yd <sup>2</sup>	ASTM D3776
Thickness	17.0	mil	ASTM D1777
Gloss Level	Matte		
Brightness	94		D65 CIE L
Substrate Color	White		
Fire Retardant	NFPA 701 Small Scale		
Printable Side	Either side is compatible for printing		

## FINISHING TIPS

Banner tape may be used to finish, but may alter the look or feel of the finished graphic. These fabric banner products may also be sewn and/or grommited, but care should be taken to avoid scratching the imaged graphic. Though not prone to fraying, a fabric hot knife can also be used to trim the edges. Be sure to let graphics fully cure before finishing. Liquid laminates can be used, but should be pre-tested as certain types can yellow and/or crack over time.

## CAUTION

Users should fully test and make their own assessment regarding product suitability.

**For more information contact your paper merchant or Mohawk Digital Specialist.**

©2017 Mohawk Fine Paper Inc., Mohawk®, and the corporate logo are registered trademarks of Mohawk.

All statements, technical information and recommendations about Mohawk products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. The purchaser must independently determine the suitability of this product for its purposes. See Mohawk Electronic Printing Guarantee for further details.

March 2017