



WIDE FORMAT INKJET PRINTABLE TEXTILES STICKY STUFF 8OZ.

engineered by AURORA®



Woven polyester textile with repositionable adhesive. Compatible with Latex, Eco-Solvent, Solvent and UV-Cured inks.

- Perfect for indoor use on painted walls, glass or other flat surfaces
- Strong enough to stay put but easily removed with no adhesive residue
- Poly coated layflat liner
- Great choice for wall murals/coverings, photo/art reproduction, POP/POS signage, home/office decor, trade show displays, life size cutouts, quick change/seasonal retail and commercial applications.

PRINTABLE TEXTILES STICKY STUFF 8OZ.

WEIGHT OZ./MIL	LINER	WIDTH INCHES	WIDTH MM	LINEAL FEET	CORE	CODE NUMBER
8.0 /20.0	90#	30	762	30	3	67-82363
	90#	54	1372	75	3	82364
	90#	60	1524	75	3	82365

Visit mohawkconnects.com for more complete stocking info.

COMPATIBILITY

LATEX	ECO-SOLVENT	SOLVENT	UV-CURED
✓✓✓	✓✓✓	✓✓✓	✓✓✓

- ✓✓✓ Excellent
✓✓ Good
✓ Fair
✗ Not Compatible

PRINTABLE TEXTILES STICKY STUFF 80Z.

TYPICAL PERFORMANCE VALUES

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material or his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Ink dry time: rapid drying depending upon type and amount of ink, relative humidity and temperature

Chemical resistance: not designed to be chemical resistant

Handling requirements: due to absorptive nature of the coating, avoid touching the coated surface with bare skin. Always wear chemical resistant gloves when handling inkjet-coated materials. Rolls are supplied with the coated surface wound out.

Durability outdoor: not designed for outdoor use

Solvent resistance: not designed to be solvent resistant

Printing temperature: 60 - 85°F / 40 - 60%RH

Display use: 60 - 85°F

Ideal storage conditions: 68 - 75°F

Shelf life: one year at ideal storage conditions, stored in original packaging

PHYSICAL CHARACTERISTICS

PROPERTY	TYPICAL VALUE	UNIT	TEST METHOD
Material	100% Polyester, 8 oz.		
Weave	Plain		
Total Weight	10.5	oz/yd ²	ASTM D3776
Thickness	20.0	mil	ASTM D1777
Liner	90	#	
Gloss Level	N/A		
Brightness	96		D65 CIE L
Coating Color	White		
Substrate Color	White		
Fire Retardant	N/A		
Printable Side	Coated side is compatible for printing		

FINISHING TIPS

Banner tape may be used to finish, but may alter the look or feel of the finished graphic. These fabric banner products may also be sewn and/or grommited, but care should be taken to avoid scratching the imaged graphic. Though not prone to fraying, a fabric hot knife can also be used to trim the edges. Be sure to let graphics fully cure before finishing. Liquid laminates can be used, but should be pre-tested as certain types can yellow and/or crack over time.

CAUTION

Users should fully test and make their own assessment regarding product suitability.

For more information contact your paper merchant or Mohawk Digital Specialist.

©2017 Mohawk Fine Paper Inc., Mohawk®, and the corporate logo are registered trademarks of Mohawk.

All statements, technical information and recommendations about Mohawk products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. The purchaser must independently determine the suitability of this product for its purposes. See Mohawk Electronic Printing Guarantee for further details.

March 2017